

Wakulla Mat™

314.546.5001

Walkway Mats Product Data Sheet

Product Specifications

Composition: Specially designed non-abrasive vinyl loop coils extruded from 100% PVC and thermally bonded. DOP free.

Fire Resistance: In accordance with:
US CPSC 16 CFR Part 1631 (FF2-70)

Tensile Strength: In accordance with:
ATSM D5034-2009
Crosswise - 3997N
Lengthwise - 3923N

Tear Strength: In accordance with:
ATSM D5034-2009
Crosswise - 1342N
Lengthwise - 1216N

Slip Resistance: In reference to GB/7100-2006
Friction Coefficient (Dry) - 0.685
Friction Coefficient (Wet) - 0.580

REACH: In accordance with EC No 1907/2006 - PASS

Packaging:
Roll Size:
3.33ft x 33.3ft
(1m x 10m)
3/8" thick
(10mm)
6 Rolls/Pallet
38 kg/Roll
219 kg/Pallet






Cleaning & Maintenance

A: If possible, hang mat with underside out. Use a soft brush or broom and warm water with anti bacterial hand soap. If you can't hang the mat, flip it over and clean the underside first.

B: Gently brush the mat until it is cleaned. Repeat for the front. Anti bacterial hand soap or mild detergent will disinfect the mat.

C: Use a hose and water to rinse the mat. Allow mat to dry completely.



Maintenance:

Mat can be easily rolled and stored. Try to keep the mat out of direct sunlight when not in use.